

DEPARTMENT OF FORESTRY AND FIRE PROTECTION OFFICE OF THE CALIFORNIA STATE FIRE MARSHAL FIRE ENGINEERING & INVESTIGATIONS DIVISION PORTABLE FIRE EXTINGUISHER PROGRAM SERVICE VEHICLE INSPECTION REPORT

Company Name:		
Physical Address:		
City:	Zip:	
Contact Person:		
VEHICLE INFORMATION	SER\	VICE PARTS
Year	↓ <u> </u>	Gauges (appropriate)
Make	▎▕▐	Discharge Nozzles (appropriate)
Model	│	Discharge Hoses (appropriate)
Color	<u> </u>	O Rings (appropriate)
Registered Owner	│	Valve Stems (appropriate)
License Number	J <u> </u>	Valve Handles and Rivets (appropriate)
	, <u> </u>	Valve Springs (appropriate)
TOOLS AND EQUIPMENT	│	Parts list for extinguisher being serviced
Brushes Non-Ferrous	│	Pull Pins
Continuity Tester (A, B, E)	↓ □	Proper recharge agent for extinguisher
Rubber Mallet	│	being serviced (i.e. ABC, BC, etc.)
Hammer	│	CO2 Horns
Screwdrivers (assorted)	│	CO2 Hoses
Wrenches (assorted)	<u> </u>	CO2 Nipples
Garden Hose	SERV	VICE SUPPLIES
Cylinder Inspection Light	│	Continuity Test Labels
Pressure Regulators &Calibrated Low-		Valve/O-Ring Lube, manufacturer approved
Pressure Gauge	┨ ├──	T 0 T
Recharge Adapters	┦ ├┼	Teflon Tape
Electric Drill and Bits	┦ ├┼	Tamper Seals
Cleaning Towels	┦ ├┼	Collar Rings (all sizes)
Clean Bucket	┦ ├┼	Maintenance Tags
Torque Wrench Set (Type A, E) *	┥ ├┼	Tape Measure
Socket Wrench Set*	┥ ├┼	Manuals*
Water Pump Pliers with smooth face jaw	┥ ├┼	Laws and Regulations (Current Edition)
Pliers (assorted) needle nose, side cutter	┥	Nitrogen/Dry Air Cylinder (secured to the
Closed Dry Chemical Recovery System	┨ ├──	vehicle per DOT Requirements) Wall Brackets
Loaner Extinguishers (10)	┤╶├┼	
Scale for extinguishers up to 60 lbs. (shall have minimum 4oz graduation, and		Toggles and Mollies
accurate to +/- 4oz) plus 10 lb. test wt.	HVDI	RO TEST EQUIPMENT
Scale for extinguishers more than 61 lbs.		Hydrostatic Testing Pump (A, C) *
(shall have minimum 8oz graduations,	 	Hydrostatic Testing Fulfip (A, C) * Hydrostatic Test Heads/Adapters (A, C) *
and accurate to +/- 8ozs) *		Safety Cage (A, C) *
Scale for extinguisher cartridges (shall	┤─├─	Cylinder Drying Unit (145 Degrees) (A, C) *
have minimum graduation not larger than		Hydrostatic Labels (A, C, E)
1/100, and accurate to +/- 1ozs) plus 1 lb.	 	Hydro Test Record Sheets (A, C, E) *
test wt.		Tryare Test Record Officets (A, O, E)
* Indicated items may be located at the shop		
D "U D (Signatura	Date:
Responsible Party	Signature	Date:
DSFM Name	Signature	Date: